



## LONKING ZZ

Code: 10801632670

## **TECHNICAL PARAMETERS**

	Bucket Capacity	0.8 m³
BASIC	Rated Payload	1500kg
	Operating Weight	5230kg
	Traction Force	52kN
	Breakout Force	35kN
	L×W×H	5925×2100×2950mm
	Manufacturer/Model	YUNNEI/YN38GB1 (Nation II )
ENGINE	Rated Power	65kW/2400rpm
	Rated Torque	285N·m/1600-1800rpm
	Transmission Type	Countershaft Powershift
	Shift Type	Fixed Shaft Hydraulic Shift Spur Gear
	Pressure of Transmission	1.1-1.5MPa
	Gear	2F/2R
	Torque Converter	Single-stage, Single-turbine, 3-element
DRIVE TRAIN	Torque Ratio	3.13
	Main Reducer	Spiral Bevel Gear Single-stage Reduction
	Final Reducer	Planetary Reduction
	Tire	16/70-20
	Travel speed-Forward	8/20km/h
	Travel speed-Reverse	8/20km/h
DDAVE	Service Brake	Air Drive, Four Wheel Brake (Dry)
BRAKE SYSTEM	Setting Pressure	0.78MPa
STSTEIN	Parking Brake	Flexible Shaft Controlled Caliper
STEERING SYSTEM	Туре	Hydraulic Load Sensor System
	Steering Pump	Shared With Working Pump
	System Pressure	14Mpa
	Steering Angle	±30°
	Туре	Pilot control
HYDRAULIC SYSTEM	Working Pump	Gear Pump
	Flow Rate	120L/min·2400rpm
	Control Valve	2 Spool
	System Pressure	16MPa
	Cycle Time (Sec)	8.2
ELECTRIC OVOTEM	System Voltage	24V
ELECTRIC SYSTEM	Battery ( 2 in series)	2x90 Ah
SERVICE REFILL CAPACITY	Fuel Tank	90L
	Hydraulic Tank	65L
		101
	Transmission	19L

## CONFIGURATION

ΥI	UNNEI Engine
L	ONKING Transmission
LC	ONKING Torque Converter
L	ONKING Drive Axle
Pi	ilot control Working System
Hi	igh Dump
Ai	ir Conditioner

## **OPTIONAL**

Bucket(1.2m³, width2.1m , 3 Piece Cutting Edges)	
Bucket(1.2m³, width2.1m , Five Detachable Teeths)	
3rd Spool for Auxiliary Function	
Hydraulic Quick Hitch	
Quick Hitch Bucket ( 3 Piece Cutting Edges)	
Quick Hitch Log Fork	
M echanical Quick Hitch	
Copper Slag Grapple	
Log Fork	
Warm Air Blower	

For more information on Lonking products, Please contact our local agent:

**LONKING HOLDINGS LIMITED** 

Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai Tel: +86-21-3760 2242 E-mail:export@lonking.cn http://www.lonkinggroup.com

65kW/2400rpm RATED POWER:

0.8m<sup>3</sup> BUCKET CAPACITY:

1500kg **■ RATED PAYLOAD:** 

OPERATING WEIGHT: 5230kg

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd. and may not be used without written p. 2020/03

The following blank can be used for notes or comments.

Specifications and design are subject to change without prior notice

